Enhancing Medical Imaging Through Data Augmentation: A Review

Beatriz Teixeira[1], Gonçalo Pinto[1], Vitor Filipe[1,2], and Ana Teixeira[1,3(✉)]

[1] University of Trás-os-Montes e Alto Douro, Quinta de Prados, 5001-801 Vila Real, Portugal
{al73263,al74081}@alunos.utad.pt, {vfilipe,ateixeir}@utad.pt
[2] INESC TEC- INESC Technology and Science, 4200-465 Porto, Portugal
[3] Mathematics centre CMAT, Pole CMAT-UTAD, Vila Real, Portugal

Abstract. This article conducts a comprehensive review of the existing literature on data augmentation and data generation techniques within the context of medical image processing. Addressing the challenges associated with building sizable medical image datasets, including the rarity of certain medical conditions, patient privacy concerns, the need for expert labeling, and the associated expenses, this review focuses on methodologies aimed at enhancing the volume and diversity of available data. Special emphasis is placed on techniques such as data augmentation and data generation, with a particular interest in their application to medical image datasets. The objective is to provide a synthesis of current research, methodologies, and advancements in this domain, offering insights into the state-of-the-art practices and identifying potential avenues for future developments in medical image data augmentation.

Keywords: Data generation · Medical Image · Image Data Augmentation

1 Introduction

In supervised learning, where classification is one of the best-known tasks, the number of labeled examples available and the results are related: the greater the number of examples, the greater the prediction capacity of the classifiers generated. However, in real-life situations, having databases with a large number of labeled examples is not always an easy task, and is often costly. In order to overcome this problem, data augmentation (DA) approaches, based on computational techniques with the aim of increasing the number of labeled examples in a data set and improve the results obtained, can be used [1]. Data warping augmentations involve transforming existing images in a way that retains their labels. This includes geometric and color transformations, random erasing, adversarial training, and neural style transfer. Oversampling augmentations create synthetic instances and incorporate them into the training set. This encompasses techniques such as mixing images, feature space augmentations, and generative adversarial networks (GANs) (Fig. 1). Developing a generative AI model

© The Author(s), under exclusive license to Springer Nature Switzerland AG 2024
O. Gervasi et al. (Eds.): ICCSA 2024 Workshops, LNCS 14816, pp. 341–354, 2024.
https://doi.org/10.1007/978-3-031-65223-3_23

for image synthesis requires a deep understanding of machine learning ideas, including deep neural networks, loss functions and optimization strategies. Deep learning methods consist of mapping input data to output data using deep neural networks and optimization algorithms. These networks, with multiple layers of interconnected neurons, learn complex patterns by adjusting the weights of the connections during training. Optimization algorithms are used to minimize the cost function, allowing the neural network to improve mapping accuracy. The backpropagation process is key to calculating gradients and adjusting weights, making deep learning effective for a variety of applications, such as image recognition [2]. Creating large medical image datasets poses significant challenges, mainly due to the infrequency of certain diseases, privacy concerns related to patient data, the necessity for expert labeling, and the high costs and labor-intensive nature of medical imaging procedures. These difficulties have spurred extensive research into image data augmentation, with a particular focus on oversampling techniques using GANs. This research is driven by the practical need for effective medical image classification applications [3].



Fig. 1. A taxonomy of image data augmentations covered; for example, meta-learning using neural style transfer is covered by neural augmentation [3].

What's left of this article is organized as follows in Sect. 2, the Materials and Methods are introduced, in Sect. 3, is made an analysis of the articles found, and in Sect. 4, the results are discussed. In Subsect. 4.1, articles focused on general algorithms will be addressed, while in Subsect. 4.2, articles focused on a specific organ will be presented. Finally, in Sect. 5, the conclusion is presented.

2 Materials and Methods

A literature review was conducted to explore the application of data generation techniques in the realm of medical image analysis. The Scopus database, a comprehensive and multidisciplinary bibliographic resource spanning various academic domains, was used for the initial phase, which involved examining scientific works on the utilization of predictive models for medical image data generation. This examination employed keywords or abbreviations such as data generation and medical image. The complete search string used was (data AND & AND generation AND & AND medical AND & AND image). Subsequently, titles and abstracts were independently scrutinized based on predefined inclusion/exclusion criteria (Table 1).

Table 1. Article selection criteria.

Stage	Selection Criteria
Identification	Total number of articles initially found
Screening	Belong to the articles category
	Year of publication between 2020 and 2023
	Full access
	English language
Eligibility	Addressing medical imaging
	Approaching the field of engineering
Included	Relating to GANs
	Interface with medical imaging

Figure 2 shows the flow diagram of the work developed, which synthesizes the review/selection process performed. This methodology aimed to provide a comprehensive overview of the current research landscape and advancements in the domain of data generation in medical image analysis.



Fig. 2. PRISMA flow diagram

3 Quantitative Analysis of the Entries

During the 2020–2023 period, several authors have developed and written about techniques that make possible to generate larger databases; thus, allowing new artificial intelligence methods to obtain better classifications and, consequently, helping health professionals to make a more effective diagnosis. The following graph (Fig. 3) helps us to understand in which years the articles were written.

A graphic representation was meticulously drawn up showing the different countries of origin of each one of the analyzed articles (Fig. 4). The importance of collaborative efforts in scientific literature should be emphasized. Articles authored by several individuals bring a wide variety of perspectives and ideas to the table. As our graphic representation vividly illustrates, the amalgamation of diverse voices from different regions creates a mosaic of knowledge.



Fig. 3. Articles organized according to year of publication.



Fig. 4. Graphic of the number of articles by country.

4 Discussion

As the demand for more accurate diagnoses and personalized treatment plans grows, there is a need for advancements in the field. This work explores the application of data augmentation techniques to enhance medical imaging outcomes. The accurate interpretation of medical images, such as MRIs, CT scans, and X-rays, is fundamental to diagnostic accuracy. Discussing the critical role of medical imaging sets the stage for understanding the need for continuous improvement in this domain. Despite the advancements in technology, challenges persist in medical imaging, including limited datasets, class imbalance, and the need for diverse representations. Acknowledging these challenges highlights the necessity for innovative solutions. Delving into the specifics, the discussion outlines how data augmentation can be effectively applied to medical imaging datasets. Exam-

ples may include enhancing the robustness of neural networks trained for image recognition and segmentation tasks. By augmenting medical imaging data, the models are better equipped to generalize across diverse cases, leading to improved performance in real-world scenarios. This section emphasizes the impact on diagnostic accuracy and treatment planning. Of all the articles that have been analyzed, these are the ones that deal with the topic of image generation for medical analysis. Many of those that were discarded only focused on image classification techniques, which are not so relevant to this topic. The articles selected for the study apply data augmentation techniques to medical images of various regions of the human body, highlighting their specific applications and benefits. Part of the analyzed articles deal with algorithms aimed at specific organs of the human body, but the other part focus on general algorithms, that explain various techniques and how they can be applied to medical images. In this sequel and in order improve the clarity of the analysis, two subsections are introduced; in each one of them are explored just the works targeting the specified type of algorithms.

4.1 Articles Focusing on General Algorithms

The articles included in Table 2, focus on the creation and improvement of specific models, algorithms or techniques aimed at solving technical challenges in areas such as medical image processing and machine learning applied to health. These articles used techniques such as Few-shot semantic segmentation, which allows images to be segmented into different classes, even when there are only a small number of training examples available for each class. This is useful in scenarios where the collection of labeled data is limited or expensive. On the other hand, DCGAN is a generative neural network architecture designed to generate realistic images, taking advantage of deep convolutions to learn high-level representations. Finally, the articles listed in Table 3, stand out for their practical application in real clinical environments, including evaluating the performance of algorithms in conjunction with medical specialists and investigating the impact of these techniques on improving clinical results. These articles cover techniques such as GANs, which are a type of generative model made up of two neural networks, the generator and the discriminator, which are trained in adversarial fashion. The generator creates samples that mimic real samples, while the discriminator tries to distinguish between the generated and real samples. This competition leads to continuous improvements in the generator's generation abilities. And also a new end-to-end architecture that is designed to simplify and optimize the GAN training process, offering a more direct and efficient approach. By integrating all training steps into a single framework, this architecture reduces model complexity and improves computational efficiency.

4.2 Articles Focusing on Specific Organs

The articles in this section also use deep learning algorithms but focus on different organs. In Table 4 the successful implementation of data augmentation in

cardiac images is discussed, emphasizing its role in improving diagnostic accuracy and optimizing cardiac diagnostic processes. Next, in Table 5 the use of these techniques in brain imaging as approached, highlighting how data augmentation contributes to significant advances in the early detection of neurological disorders. Both articles deal with GAN-based techniques. In the context of lung imaging, in Table 6 the progress made with the application of data augmentation as highlighted, offering valuable insights for the early diagnosis of respiratory diseases. Exploring other anatomical regions, Table 7 focuses on the analysis of bowel images, emphasizing the gains provided by data augmentation in accurately identifying gastrointestinal conditions. In addition, in Table 8 advances in the analysis of eye images are focused, highlighting how data augmentation has contributed to a better understanding and showing of ophthalmic diseases. The

Table 2. Features of studies on model and technique development in medical image processing and machine learning for health.

Article	Author	Year	Country	Study aim
A dynamic few-shot learning framework for medical image stream mining based on self-training [4]	Zhengqiang Ye, and Wei Zhang	2023	China	Few-shot semantic segmentation (FSS) has been widely used in the field of information medicine and intelligent diagnosis. Due to the high cost of collecting medical data and protecting patient privacy, it is difficult to obtain labeled medical images. To address this issue, the authors propose a few-shot dynamic learning framework for medical semantic segmentation, which can fully utilize the characteristics of the newly collected/generated data stream. Experiment results show a significant performance gain in extracting medical data streams compared to the baseline method.
Empirical Analysis of Deep Convolutional Generative Adversarial Network for Ultrasound Image Synthesis [5]	Dheeraj Kumar, Mayuri A. Mehta, Indranath Chatterjee	2021	India and South Korea	In this article, is present an empirical analysis of the state-of-the-art Deep Convolutional Generative Adversarial Network (DCGAN) for the synthesis of ultrasound images. The results show that good quality synthetic ultrasound images are generated within 100 training epochs of the DCGAN. The quality of the synthetic ultrasound images is evaluated using Mean Squared Error (MSE), Peak Signal to Noise Ratio (PSNR) and Structural Similarity Index (SSIM).
Generating and Weighting Semantically Consistent Sample Pairs for Ultrasound Contrastive Learning [6]	Yixiong Chen, Chunhui Zhang, Chris H.Q. Ding, Li Liu	2022	China	This study presents a solution for the costly creation of large, well-crafted medical datasets by introducing a positive pair generation module and an automatic sample weighting module based on meta-learning. Experimental results across multiple computer-aided diagnosis tasks show that the proposed self-supervised method achieves state-of-the-art performance

Table 3. Characteristics of studies focusing on clinical applications and performance evaluation.

Article	Author	Year	Country	Study aim
Chronic Wound Image Augmentation and Assessment Using Semi-Supervised Progressive Multi-Granularity EfficientNet [7]	Ziyang Liu, Emmanuel Agu, Peder Pedersen, Clifford Lindsay, Bengisu Tulu, Diane Strong	2023	USA	This study utilizes semi-supervised learning to augment a small, unbalanced wound dataset with a secondary dataset and applies the augmented dataset for deep learning-based wound assessment. Employing progressive multi-granular training and a secondary corpus of 9870 unlabeled wound images, the study finds that generating synthetic wound images using Generative Adversarial Networks (GAN) does not improve wound assessment.
Hierarchical Amortized GAN for 3D High Resolution Medical Image Synthesis [8]	Li Sun, Junxiang Chen, Yanwu Xu, Mingming Gong, Ke Yu, Kayhan Batmanghelich	2022	USA and Australia	In this work, the authors propose a new end-to-end GAN architecture that can generate high-resolution 3D images. Experiments with 3D chest CT and brain MRI demonstrate that our approach surpasses the state of the art in image generation. The article also demonstrate clinical applications of the proposed model in data augmentation and the extraction of clinically relevant features.
Inverse Heat Dissipation Model for Medical Image Segmentation [9]	Yu Kashihara, Takashi Matsubara	2023	Japan	The diffusion model has achieved success in generating and editing high-quality images due to its ability to produce fine detail. Its superior generation capacity has the potential to facilitate more detailed segmentation. The proposed method involves generating a mask that gradually shrinks to fit the shape of the desired segmentation region. The results show that the proposed method outperforms existing methods and provides more detailed segmentation.
Learning From Limited and Imbalanced Medical Images With Finer Synthetic Images From GANs [10]	Xiaoli Qin, Francis M. Bui, Ha H. Nguyen, Zhu Han	2022	Canada, USA, South Korea	This article represents one of the first comprehensive investigations into the impact of synthetic image generation on classifier performance, elucidated empirically through a comparative analysis of a simple deep convolutional GAN with a more complex progressive GAN design. The results obtained show that the use of more detailed images synthesized by GANs with the proposed multiscale CNN achieved good classification performance, under a wide variety of operating conditions.
SSIS-Seg: Simulation-Supervised Image Synthesis for Surgical Instrument Segmentation [11]	Emanuele Colleoni, Dimitris Psychogyios, Beatrice Van Amsterdam, Francisco Vasconcelos, Danail Stoyanov	2022	UK	In this paper, is present a new method for generating surgical images that can fuse robotic instrument simulation and recent domain adaptation techniques to synthesize artificial surgical images for training surgical instrument segmentation models. The authors provide an extensive evaluation of our method in terms of segmentation performance, along with a validation study of image quality using evaluation metrics. In addition, was released a new segmentation dataset of real surgeries that will be shared for research purposes.
The Effectiveness of Data Augmentation for MatureWhite Blood Cell Image Classification in Deep Learning Selection of an Optimal Technique for Hematological Morphology Recognition [12]	Hiroyuki Nozaka, Kosuke Kamata, Kazufumi Yamagata	2023	Japan	The data augmentation method is known as a useful technique for generating a dataset with a large number of images from a set with a small number of images for supervised training in deep learning. However, a data augmentation method with low validity for image recognition was reported in a recent study on artificial intelligence (AI). This study aimed to clarify the optimal data augmentation method in deep learning model generation for white blood cell (WBC) recognition. Although data augmentation methods are often used to achieve high accuracy in the generation of AI with supervised training, the authors believe that it is necessary to select the optimal data augmentation method for the generation of medical AI based on the characteristics of medical images

Table 4. Characteristics of studies on data augmentation in cardiac images.

Article	Author	Year	Country	Study aim
A Domain Translation Framework With an Adversarial Denoising Diffusion Model to Generate Synthetic Datasets of Echocardiography Images [13]	Cristiana Tiago, Sten Roar Snare, Jurica Šprem, and Kristin McLeod	2023	Norway	Translation operations in the field of medical imaging are currently in high demand from researchers and clinicians. Among other capabilities, this task allows the generation of new medical images with a sufficiently high image quality, making them clinically relevant. The proposed framework is based on an adversarial Denoising Diffusion Model (DDM) to synthesize echocardiography images and perform domain translation. Unlike Generative Adversarial Networks (GANs), DDMs are capable of generating high quality image samples with great diversity. If a DDM is combined with a GAN, this ability to generate new data is completed with an even faster sampling time.
A Framework for Simulating Cardiac MR Images with Varying Anatomy and Contrast [14]	Sina Amirrajab, Yasmina Al Khalil, Cristian Lorenz, Jürgen Weese, Josien Pluim, Marcel Breeuwer	2023	Netherlands and Germany	One of the limiting factors for the development and adoption of new medical image analysis methods based on deep learning (DL) is the scarcity of labeled medical images. In this paper, was developed a flexible framework for simulating cardiac magnetic resonance (MR) images with varying anatomical and imaging characteristics, with the aim of creating a diverse virtual population. The proposed framework is optimized to generate a substantial number of cardiac MRI images with ground truth labels suitable for downstream supervised tasks. A database of virtual subjects is simulated and its usefulness in assisting a DL segmentation method is evaluated.
Development of anthropomorphic mathematical phantoms for simulations of clinical cases in diagnostic nuclear medicine [15]	Natalya Denisova, Marina Ondar, Hunor Kertesz, Thomas Beyer	2022	Russia and Austria	The aim was to propose a new generation of mathematically stylized phantoms with high levels of anatomical detail for the purposes of SPECT and PET simulations. Both phantoms produced realistic planar images, which closely mimic real clinical planar images. The images obtained in SPECT computer simulation of myocardial perfusion with a virtual patient (MMT) show the same errors and interpretation problems that exist in clinical routine. These phantoms can be used for clinical case simulations to help medical specialists understand the causes of artifacts and biases in PET and SPECT images.
Generating Synthetic Labeled Data from Existing Anatomical Models: An Example with Echocardiography Segmentation [16]	Andrew Gilbert, Maciej Marciniak, Cristobal Rodero, Pablo Lamata, Eigil Samset, Kristin McLeod	2021	UK and Norway	Instead of labeling images, in this paper was proposed an alternative approach where images are generated from existing high-quality annotations using generative adversarial networks (GANs). The authors demonstrate the approach by generating synthetic 2D echocardiography images for comparison with existing ultrasound segmentation datasets using deep learning. The results demonstrate that the images produced can be effectively used in place of real data for training. The proposed approach paves the way for the automatic generation of training data for many medical imaging tasks, as the same process can be applied to other segmentation or landmark detection tasks in any modality

articles present solutions for the automatic detection of diabetic retinopathy in retinal images. The application of these techniques to the analysis of chromosomal images is discussed in Table 9, where the potential of data augmentation in the presented genetic conditions and chromosomal disorders is emphasized. Skin image analysis is covered in Table 10, highlighting how data augmentation

Table 5. Characteristics of studies on data augmentation in brain imaging.

Article	Author	Year	Country	Study aim
A Transfer Deep Generative Adversarial Network Model to Synthetic Brain CT Generation from MR Images [17]	Yi Gu, Qiankun Zheng	2021	China	Medical imaging aims to convert existing medical images into one or more required medical images, reducing the time needed to diagnose samples and the exposure of the human body to radiation from multiple medical images. The model proposed in this article is called Dual3DPatchGAN and is based on transfer learning. This model does not require one-to-one paired data sets, offering a more flexible approach. It addresses the limitations of DualGAN by eliminating bar-shaped "shadows" in 3D images and allowing bidirectional conversion between the two types of medical images. The experimental results indicate that Dual3DPatchGAN is more suitable for generating medical images compared to other models, showing better quality in the images generated.
BrainGAN: Brain MRI Image Generation and Classification Framework Using GAN Architectures and CNN Models [18]	Halima Hamid N. Alrashedy, Atheer Fahad Almansour, Dina M. Ibrahim, Mohammad Ali A. Hammoudeh	2022	Saudi Arabia and Egypt	The lack of magnetic resonance images (MRI) of the brain makes it difficult to classify brain tumors using image-based classification. The solution to this challenge has been achieved by applying augmentation techniques based on Generative Adversarial Network (GAN). In this article, a framework, called BrainGAN, is proposed for generating and classifying MRI images of the brain using GAN architectures and deep learning models

Table 6. Characteristics of studies on data augmentation in respiratory imaging.

Article	Author	Year	Country	Study aim
CycleGAN Clinical Image Augmentation Based on Mask Self-Attention Mechanism [19]	Junzhuo Liu, Zhixiang Wang, Ye Zhang, Alberto Traverso, Andre Dekker, Zhen Zhang, Qiaosong Chen	2022	China and Netherlands	To overcome the lack and imbalance of data, this article was focused on generating and balancing data on radiation-induced pneumonia, an extremely rare disease with a low incidence. To deal with the aforementioned problems, the method used by previous researchers often involves using generative models to generate data to complement the sparse samples to achieve a balanced distribution of data samples. Among various generative models, CycleGAN is widely used in medical imaging due to its cyclic consistency to perform style migration without changing the basic content.
Synthesis of COVID-19 chest X-rays using unpaired image-to-image translation [20]	Hasib Zunair, A. Ben Hamza	2021	Canada	Motivated by the lack of publicly available datasets of chest X-rays of positive patients with coronavirus disease 2019 (COVID-19), the authors built the first open dataset of high-fidelity synthetic images of COVID-19 chest X-rays, using an unsupervised domain adaptation approach through class conditioning and adversarial training. In addition, the proposed data generation framework offers a viable solution for COVID-19 detection in particular and for medical image classification tasks in general

has promoted a more comprehensive and accurate analysis of dermatological diseases. Table 11 explores the opportunities in breast image analysis, demonstrating how data augmentation can play a crucial role in the early detection of breast and lung conditions.

Table 7. Characteristics of studies on data augmentation for gastrointestinal condition identification in bowel images.

Article	Author	Year	Country	Study aim
Data augmentation for computed tomography angiography via synthetic image generation and neural domain adaptation [21]	Malte Seemann, Lennart Bargsten, Alexander Schlaefer	2020	Germany	In the field of medical imaging, annotations are not only scarce, but also often not entirely reliable. To address both challenges, a two-step approach was developed to generate realistic synthetic CTA data for the purpose of data augmentation. The impact of synthetic data on lumen segmentation using convolutional neural networks (CNNs) is evaluated, and the resulting performances compared

Table 8. Characteristics of studies on data augmentation in eye image analysis.

Article	Author	Year	Country	Study aim
Data augmentation for improving proliferative diabetic retinopathy detection in eye fundus images [22]	Teresa Araújo, Guilherme Aresta, Luís Mendonça, Susana Penas, Carolina Maia, Ângela Carneiro, Ana Maria Mendonça, Aurélio Campilho	2020	Portugal	Public datasets labeled for diabetic retinopathy have a small representation of images of the most severe grades of the disease, and thus there is a lack of PDR cases to train diabetic retinopathy classification models. The authors propose a heuristic-based data augmentation scheme, which is based on the synthesis of neovessel (NV)-like structures, to compensate for the lack of PDR cases in labeled diabetic retinopathy datasets. The proposed algorithm for generating neovessels is based on general knowledge about the common location and shape of these structures.
Exudate Detection: Integrating Retinal-Based Affine Mapping and Design Flow Mechanism to Develop Lightweight Architecture [23]	Muhammad Hussain	2023	UK	This article presents an innovative solution to the critical challenges in the automatic detection of diabetic retinopathy using fundus images. To combat the scarcity of data, the authors investigated the process of modeling fundus images, proposing the "Retina-Based Affine Mapping" mechanism. This mechanism facilitated the generation of representative augmentations to model occurrences influenced by various internal and external factors during the acquisition of fundus images, diverging from the concept of previous work centered on generic augmentations focused mainly on data scaling and not on representation augmentation

Table 9. Characteristics of studies on data augmentation in chromosomal image analysis.

Article	Author	Year	Country	Study aim
Deep Anomaly Generation: An Image Translation Approach of Synthesizing Abnormal Banded Chromosome Images [24]	Lukas Uzolas, Javier Richo, Pierrick Coupé, Juan C. Sanmiguel, György Cserey	2022	Spain, France and Hungary	In the case of banded chromosome images, creating sufficiently large libraries is difficult for many pathologies due to the rarity of certain genetic diseases. Generative Adversarial Networks (GANs) have proved effective in generating synthetic images and expanding training data sets. In this work, the authors implemented a conditional GAN (cGAN) that allows the generation of realistic images of individual chromosomes following user-defined banding patterns

Table 10. Characteristics of studies on data augmentation in skin image analysis.

Article	Author	Year	Country	Study aim
Deep Convolutional Generative Adversarial Networks to Enhance Artificial Intelligence in Healthcare: A Skin Cancer Application [25]	Marco La Salvia, Emanuele Torti, Raquel Leon, Himar Fabelo, Samuel Ortega, Beatriz Martinez-Veja, Gustavo M. Callico, Francesco Leporati	2022	Italy, Spain and Norway	The lack of large data sets to train the models effectively limits the applications of DL in the medical field. Thus, its use with hyperspectral images is still at an early stage. The authors propose a generative adversarial deep convolutional network to generate synthetic hyperspectral images of epidermal lesions, aiming at skin cancer diagnosis and overcoming the challenges of small datasets to train DL architectures. Experimental results show the effectiveness of the proposed structure, capable of generating synthetic data to train DL classifiers

Table 11. Characteristics of studies on data augmentation in breast image analysis.

Article	Author	Year	Country	Study aim
GANs for generation of synthetic ultrasound images from small datasets [26]	Lennart Maack, Lennart Holstein, Alexander Schlaefer	2022	Germany	Generative adversarial networks (GAN) are capable of generating high-quality synthetic images. This paper investigates the capabilities of different state-of-the-art GAN architectures in generating realistic breast ultrasound images if only a small amount of training data is available. In conclusion, GANs can be successfully used to generate synthetic ultrasound images of high quality and diversity, improve the classification performance of CNNs and thus provide a benefit for computer-aided diagnosis

5 Conclusion

The integration of data augmentation techniques into the field of medical imaging marks a significant step forward in improving diagnostic accuracy and treatment efficacy. By overcoming challenges related to limited data sets and increasing model robustness through augmentation, we pave the way for a more versatile and reliable health imaging infrastructure.

This discussion highlights the fundamental role of augmented data in empowering machine learning models to discern subtle patterns, leading to better generalization across a range of clinical scenarios. However, it is important to recognize that traditional techniques, such as rotation, translation and brightness adjustments, also play an essential role in preparing datasets for model training.

When comparing traditional techniques with generative approaches such as GANs, it is important to consider the advantages and disadvantages of each. For example, while traditional techniques may be simpler to implement and interpret, GANs have the potential to generate more realistic and diverse data. However, GANs also face unique challenges, such as the difficulty in finding a balance point between the discriminator and the generator, which can lead to problems with convergence and the quality of the results.

Looking to the future, the synergy between medical imaging and data augmentation has enormous potential. The ongoing evolution of artificial intelligence

and machine learning in healthcare is set to redefine the boundaries of diagnostic accuracy. As we navigate this intersection, it is imperative to foster a collaborative approach, involving clinicians, researchers and technologists, to ensure that advances in medical imaging translate into tangible benefits for patient care and outcomes.

Acknowledgments. The research was partially financed by the Portuguese Funds through FCT (Fundação para a Ciência e a Tecnologia), within the Projects UIDB/00013/2020 and UIDP/00013/2020.

References

1. Luke, T., Geoff, N.: Improving deep learning using generic data augmentation. In: IEE SYMPOSIUM 2018, Bangalore, India, pp. 1542–1547 (2018). https://doi.org/10.1109/SSCI.2018.8628742
2. Tewari, A., et al.: State of the art on neural rendering. Comput. Graph. Forum **32**(2), 701–727 (2020)
3. Connor, S., Taghi, K.: A survey on image data augmentation for deep learning. J. Big Data **6**(1), 1–48 (2019)
4. Zhengqiang, Y., Wei, Z.: A dynamic few-shot learning framework for medical image stream mining based on self-training. EURASIP J. Adv. Signal Process. **2023**(1), 49 (2023)
5. Dheeraj, K., Mayuri A, M., Indranath, C.: Empirical analysis of deep convolutional generative adversarial network for ultrasound image synthesis. Open Biomed. Eng. J. **15**(1) (2021)
6. Yixiong, C., Chunhui, Z., Chris, H.Q.D., Li, L.: Generating and weighting semantically consistent sample pairs for ultrasound contrastive learning. IEEE Trans. Med. Imaging **42**, 1388–1400 (2022)
7. Ziyang, L. et al.: Chronic wound image augmentation and assessment using semi-supervised progressive multi-granularity EfficientNet. IEEE Open J. Eng. Med. Biol. 1–17 (2023) https://doi.org/10.1109/OJEMB.2023.3248307
8. Li, S., et al.: Hierarchical amortized GAN for 3D high resolution medical image synthesis. IEEE J. Biomed. Health Inf. **26**(8), 3966–3975 (2022)
9. Yu, K., Takashi, M.: Inverse heat dissipation model for medical image segmentation. IEICE Trans. Inf. Syst. **106**(11), 1930–1934 (2023)
10. Xiaoli, Q., et al.: Learning from limited and imbalanced medical images with finer synthetic images from GANs. IEEE Access **10**, 91663–91677 (2022)
11. Emanuele, C., Dimitris, P., et al.: SSIS-SEG: simulation-supervised image synthesis for surgical instrument segmentation. IEEE Trans. Med. Imaging **41**(11), 3074–3086 (2022)
12. Hiroyuki, N., Kosuke, K., Kazufumi, Y.: The effectiveness of data augmentation for mature white blood cell image classification in deep learning-selection of an optimal technique for hematological morphology recognition-. IEICE Trans. Inf. Syst. **106**(5), 707–714 (2023)
13. Cristiana, T., Sten, S., Jurica, S., Kristin, M.: A domain translation framework with an adversarial denoising diffusion model to generate synthetic datasets of echocardiography images. IEEE Access **11**, 17594–17602 (2023)
14. Sina, A., et al.: A framework for simulating cardiac MR images with varying anatomy and contrast. IEEE Trans. Med. Imaging **42**(3), 726–738 (2022)

15. Natalya, D., Marina, O., Hunor, K., Thomas, B.: Development of anthropomorphic mathematical phantoms for simulations of clinical cases in diagnostic nuclear medicine. Comput. Methods Biomech. Biomed. Eng. Imaging Visualizat. **11**(3), 433–441 (2023)
16. Andrew, G., et al.: Generating synthetic labeled data from existing anatomical models: an example with echocardiography segmentation. IEEE Trans. Med. Imaging **40**(10), 2783–2794 (2021)
17. Yi, G., Qiankun, Z.: A transfer deep generative adversarial network model to synthetic brain CT generation from MR images. Wirel. Commun. Mob. Comput. **2021**, 1–10 (2021)
18. Halima, H., et al.: BrainGAN: brain MRI image generation and classification framework using GAN architectures and CNN models. Sensors **22**(11), 4297 (2022)
19. Junzhuo, L., et al.: CycleGAN clinical image augmentation based on mask self-attention mechanism. IEEE Access **10**, 105942–105953 (2022)
20. Hasib, Z., A Ben, H.: Synthesis of COVID-19 chest X-rays using unpaired image-to-image translation. Social Netw. Anal. Mining **11**, 1–12 (2021)
21. Malte, S., Lennart, B., Alexander, S.: Data augmentation for computed tomography angiography via synthetic image generation and neural domain adaptation. De Gruyter (2020)
22. Teresa, A., et al.: Data augmentation for improving proliferative diabetic retinopathy detection in eye fundus images. IEEE Access **8**, 182462–182474 (2020)
23. Muhammad, H.: Exudate detection: integrating retinal-based affine mapping and design flow mechanism to develop lightweight architectures. IEEE Access **11**, 125185–125203 (2023)
24. Lukas, U., et al.: Deep convolutional generative adversarial networks to enhance artificial intelligence in healthcare: a skin cancer application. IEEE Access **10**, 59090–59098 (2022)
25. Marco, L.S., et al.: Deep convolutional generative adversarial networks to enhance artificial intelligence in healthcare: a skin cancer application. Sensors **22**(16), 16 (2022)
26. Lennart, M., Lennart, H., Alexander, S.: GANs for generation of synthetic ultrasound images from small datasets. Curr. Direct. Biomed. Eng. **8**(1), 17–20 (2022)